

MATERIAL SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME	LOCK THE TOP SELF-LEVELLING UNDERLAYMENT- PART B		
PRODUCT USE	ACTIVATOR FOR CONCRETE REPAIR MATERIAL		
MANUFACTURER'S NAME	Specialty Products Group 6254 SKYWAY RD SMITHVILLE, ONTARIO L0R 2A0 CANADA	TEL: 1-877-957-4626 FAX: 905-527-0606	
SUPPLIER'S NAME	SEE MANUFACTURER		
EMERGENCY NUMBER	613-996-666 OR *666 CANUTER 1-800-535-5053 UNITED STATES POISON INFORMATION CENTER		
MSDS REVISION DATE	September 2, 2014		

2. COMPOSITION/INFORMATION ON THE COMPONENTS

COMPONENT NAME	CAS #	TLV	CONCENTRATION %
NO HAZARDOUS INGREDIENTS	N/A	N/A	N/A

3. HAZARD IDENTIFICATION

HEALTH EFFECTS	May cause irritation to skin, eyes, and respiratory tract. May be harmful if swallowed
----------------	--

4. FIRST AID MEASURES

FIRST AID – EYE	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.
FIRST AID – SKIN	Flush the skin with water and soap if irritation develops.
FIRST AID – INGESTION	Rinse mouth out with water. If person is conscious, dilute stomach contents with water and induce vomiting
FIRST AID – INHALATION	Remove from exposure.

5. FIRE FIGHTING MEASURES

FIRE HAZARDS	Non-flammable. Used as a fire-retardant
--------------	---

6. ACCIDENTAL RELEASE MEASURES

SPILLAGE	If spilled floor may be slippery, use care to avoid falling. Dike and contain spill with inert material e.g. sand or earth. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep spill and cleaning run-offs out of municipal sewers and open bodies of water.
----------	--

7. HANDLING AND STORAGE

HANDLING	Avoid using containers, pipes and fittings made of zinc-clad or copper bearing alloys that are corroded by ammonia.
----------	---

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROL MEASURES	No ventilation is required.
RESPIRATORY PROTECTION	None normally required.
HAND PROTECTION	If irritation develops wear long sleeve gloves.
EYE PROTECTION	Chemical splash goggles (ANSIZ.1 or approved equivalent)
BODY PROTECTION	Clothing should cover body adequately to prevent exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE	Liquid
COLOR	Blue
ODOR	Odorless
PH	6-8
SPECIFIC GRAVITY	1.1- 1.2
BOILING RANGE/POINT (°C/F)	104 ⁰ -110C
FLASH POINT (PMCC) (°C/F)	N//A
EXPLOSION LIMITS (%)	N/A
VAPOR PRESSURE	N/A
SOLUBILITY IN WATER	Completely soluble
VAPOR DENSITY (AIR = 1)	N//A
EVAPORATION RATE	None
VOC (g/l)	0

10. STABILITY AND REACTIVITY

STABILITY	Stable.
MATERIALS TO AVOID (INCOMPATIBILITY)	Zinc clad and copper bearing alloys. Water reactivates materials.
HAZARDOUS POLYMERIZATION	Will not occur
HAZARDOUS DECOMPOSITION PRODUCTS	None

11. TOXICOLOGICAL INFORMATION

EYES	Irritation to eyes
SKIN	None listed
INHALATION	Not generally considered an inhalation hazard
INGESTION	May cause nausea or diarrhea. Low oral toxicity

12. ECOLOGICAL INFORMATION

MOBILITY	Treat as phosphate
PERSISTENCE/DEGRADABILITY	Biodegradable
BIO-ACCUMULATION	May bio-accumulate.
ECOTOXICITY	Ingredients classified as 4B ingredients by EPA (inert ingredients)

13. DISPOSAL

WASTE DISPOSAL	If uncontaminated \, recover and re-use. Landfill or incinerate the solids and the contaminated dyking material according to local, state or federal regulations.
----------------	---

14. TRANSPORTATION INFORMATION

DOT CFR 172.101 DATA	Not regulated
UN PROPER SHIPPING NAME	Not regulated
UN CLASS	Not regulated
UN NUMBER	Not regulated
UN PACKAGING GROUP	Not regulated

15. REGULATORY INFORMATION

WHMIS CLASSIFICATION	Not controlled
----------------------	----------------

16. OTHER INFORMATION

NFPA RATINGS	NFPA CODE for Flammability 0 NFPA CODE for Health 1 NFPA CODE for Reactivity 0
--------------	--

	NFPA CODE for Special Hazards none
ABBREVIATIONS	N/A: Denotes no applicable information found or available CAS#: Chemical Abstracts Service Number ACGIH: American Conference of Governmental Industrial Hygienists OSHA: Occupational Safety and Health Administration TLV: Threshold Limit Value PEL: Permissible Exposure Limit STEL: Short Term Exposure Limit NTP: National Toxicology Program IARC: International Agency for Research on Cancer R: Risk S: Safety LD50: Lethal Dose 50% LC50: Lethal Concentration 50%
PREPARED BY:	Specialty Products Group Inc.

Provided data is offered in good faith as typical values and not as a product specification. No warranty, either express or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable, however, each user should review these recommendations.